

## SECTION 1: Identification

### 1.1. Identification

Product form : Mixture  
Product name : EP17-Grout Part A

### 1.2. Recommended use and restrictions on use

No additional information available

### 1.3. Supplier

Echem  
4102 El Rey Road SE  
Albuquerque, New Mexico  
United States  
T (505) 832-3667 - F (505) 217-3721  
<https://e-chem.net/>

### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300  
For Chemical Emergency Call Chemtrec 24hr/day 7days/week  
Within USA and Canada: 1-800-424-9300  
Outside USA and Canada: 703-527-3887  
(collect calls accepted)

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture


#### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H401 - Toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P391 - Collect spillage.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Bisphenol A diglycidyl ether resin	CAS-No.: 1675-54-3	< 100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
butanedioldiglycidyl ether	CAS-No.: 2425-79-8	≥ 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### EP17-Grout Part A

No additional information available

#### Bisphenol A diglycidyl ether resin (1675-54-3)

No additional information available

#### butanedioldiglycidyl ether (2425-79-8)

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Mixture contains one or more component(s) which have the following colour(s):  
Yellow-brown Yellow Colourless

Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.

Mixture contains one or more component(s) which have the following odour:  
Mild odour Aromatic odour

Odor threshold : No data available

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
LD50 oral rat	> 2000 mg/kg body weight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	22736 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	23200 mg/kg
ATE US (oral)	22736 mg/kg body weight
ATE US (dermal)	23200 mg/kg body weight

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LD50 oral rat	1134 mg/kg Source: National Library of Medicine
LD50 oral	1120 mg/kg
LD50 dermal rat	> 2150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	1130 mg/kg Source: National Library of Medicine
LD50 dermal	2150 mg/kg
ATE US (oral)	1120 mg/kg body weight
ATE US (dermal)	1130 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
pH	No data available in the literature

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
pH	7 (100 %)

Serious eye damage/irritation : Causes serious eye irritation.

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
pH	No data available in the literature

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
pH	7 (100 %)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
Viscosity, kinematic	No data available in the literature
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Viscosity, kinematic	15.2 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
EC50 - Crustacea [1]	1.7 mg/l
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LC50 - Fish [1]	13 mg/l
EC50 - Crustacea [1]	22 mg/l Source: National Institute of Technology and Evaluation
EC50 72h - Algae [1]	> 93 mg/l Source: National Institute of Technology and Evaluation
NOEC chronic algae	29 mg/l

### 12.2. Persistence and degradability

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
BCF - Other aquatic organisms [1]	31 (QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value, EU Method A.8: Partition Coefficient, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.15
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
Surface tension	58.7 – 58.9 mN/m (20 °C, EU Method A.5: Surface tension)

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Bisphenol A diglycidyl ether resin (1675-54-3)</b>	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Mobility in soil	0.48 Source: Quantitative Structure Activity Relation

### 12.5. Other adverse effects

No additional information available





## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
3082	UN3082	3082	3082
<b>14.2. Proper Shipping Name</b>			
Environmentally hazardous substances, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A diglycidyl ether resin ; butanedioldiglycidyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A diglycidyl ether resin ; butanedioldiglycidyl ether)	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A diglycidyl ether resin ; butanedioldiglycidyl ether)
<b>14.3. Transport hazard class(es)</b>			
9	9	9	9
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			
<b>14.6. Special precautions for user</b>			

Special transport precautions : As per 49 CFR 171.4(c)(1) packaging requirements do not apply to this product if shipped in non-bulk packaging and is not shipped via vessel for domestic travel.



# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### DOT

UN-No.(DOT)	:	UN3082
DOT Special Provisions (49 CFR 172.102)	:	8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	155
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	No Limit
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### TDG

UN-No. (TDG) : UN3082

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171
<b>IMDG</b>	
Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
<b>IATA</b>	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197, A215

# EP17-Grout Part A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA) : 9L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

#### Bisphenol A diglycidyl ether resin (1675-54-3)

Listed on the Canadian DSL (Domestic Substances List)

#### butanedioldiglycidyl ether (2425-79-8)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.